

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

12

EUROPEAN PATENT APPLICATION

21 Application number: 82102030.2

51 Int. Cl.³: A 61 B 5/14

22 Date of filing: 13.03.82

30 Priority: 23.03.81 US 246523

43 Date of publication of application:
29.09.82 Bulletin 82/39

84 Designated Contracting States:
BE DE FR GB IT NL SE

71 Applicant: Becton, Dickinson and Company
Mack Centre Drive
Paramus New Jersey 07652(US)

72 Inventor: Burns, James A.
1104 Kipling Road
Elizabeth New Jersey(US)


74 Representative: Selting, Günther, Dipl.-Ing. et al,
Deichmannhaus am Hauptbahnhof
D-5000 Köln 1(DE)

54 Automatic retractable lancet assembly.

57 An automatic retractable lancet assembly (20) includes a housing (22) with a sharp-pointed lancet (24) movably mounted therein. A depressible plunger (30) and slide mechanism actuates the movement of the lancet (24) outwardly from the housing (22). After this outward movement is completed, the actuator elements become dissociated from further movement of the lancet (24). Subsequently, the lancet (24) is automatically retracted back inside the housing (22) by virtue of a spring element (28).

EP 0 061 102 A2

/...



1
a
i
5
a
F
V
1
10
15
20
25
30

AUTOMATIC RETRACTABLE LANCET ASSEMBLYBACKGROUND OF THE INVENTION

1. Field of the Invention. The present invention relates to a lancet assembly, and more particularly, concerns an automatic retractable lancet assembly useful in penetrating the skin of a patient.

5 2. Description of the Prior Art. Sharp-pointed lancets are employed to make a quick puncture or penetration of the patient's skin in order to provide a small outflow of blood. Various tests may be employed with only small amounts of blood so that the blood flowing from a finger prick is
10 normally sufficient. However, due to the sensitive nerve endings in the finger tip area, this procedure could induce a significant amount of pain in the patient even though the skin puncture produces minimal cutting. In order to minimize potential pain, it is desirable to make the thrust of the
15 lancet through the patient's skin rapidly.

Spring-loaded lancets of different types and forms have been well known and are typified, for example, by U. S. Patent Nos. 55,620; 1,135,465; 3,030,959; 4,139,011; 4,203,446; 4,230,118; Swedish Patent No. 124247 and Sutor,
20 A. H., et al., "Bleeding From Standardized Skin Punctures: Automated Technique for Recording Time, Intensity and Pattern of Bleeding," A. J. C. P., Volume 55, May 1971.

U. S. Patent No. 4,203,446, above, is significant in that it teaches the puncture of the skin of a patient with
25 a lancet which is retracted back into the device after piercing the patient's skin. In the patented device, the downward motion of the lancet is initiated by the impact of a spring-loaded hammer, and as this motion continues, the spring potential decreases. At the time of impact, the
30 return spring begins to compress and increase potential energy. When the potential energy in the return spring under compression exceeds the potential energy in the

driving spring, compression of the return spring ends and decompression begins. This, then, reverses the motion of the lancet. However, impact is necessary to compress the return spring and increase its potential energy rapidly. Without the impact force, the spring forces would approach equilibrium and then there would be no reverse motion in order to retract the lancet out of the patient's skin. Furthermore, since spring potential is critical in this patented device, a conical spring is relied upon to overcome recoil due to the surge of the larger return spring. Despite the foregoing inventions, improvements in this field of lancets are still being sought.

SUMMARY OF THE INVENTION

An automatic retractable lancet assembly of the present invention comprises a housing with a sharp-pointed lancet movably mounted therein. Actuating means moves the lancet outwardly from the housing and thereafter becomes dissociated from further movement of the lancet. Subsequent to this outward movement of the lancet, operable means is provided for automatically retracting the lancet back inside the housing.

In the preferred embodiment of the present invention, the housing includes an aperture with the lancet mounted in the housing so that its point lies adjacent the interior side of the aperture. A depressible plunger is movably mounted in the housing in the end thereof opposite from the lancet. Also mounted inside the housing is a first spring in a compressed condition adapted to decompress upon the plunger being depressed into the housing. This causes the movement of the lancet outward of the aperture for penetration of the skin of a patient. The first spring is adapted to become dissociated from the lancet after the lancet completes its outward movement. A second spring is mounted inside the housing in a substantially decompressed condition before the plunger is depressed. This second spring is adapted to become compressed during outward movement of the

and
n of
the
ly.
roach
in
is
ver-
ing.
s
present
cet
ncet
ent
is
inside
ion,
ed in
or
the
ing
e
the
tra-
pted
com-
tion
the

lancet. Furthermore, the second spring is adapted to decompress when the first spring becomes dissociated from the lancet. This causes the lancet to be automatically retracted back inside the housing.

5 In accordance with the principles of the present invention, the desired functions are achieved by virtue of structure which is notably different from the structure of prior art lancet assemblies. In particular, and in the preferable embodiment, two springs are employed to complete the intended purpose of the lancet. The first spring
10 serves as a driving spring to rapidly thrust the lancet outwardly for penetration of the patient's skin. At this time, this driving spring becomes dissociated from movement of the lancet. The second spring serves as a return spring, operable after the driving spring has become so dissociated.
15 Therefore, when the second or return spring automatically retracts the lancet back into the housing, there is no opposing spring force, such as found in U. S. Patent No. 4,203,446. Thus, in the present invention, the various
20 spring potential energies do not have to balance as in the aforementioned patented invention. The return spring of the present invention only has to be sufficiently strong to retract the lancet inwardly. Therefore, considerations of balancing spring forces, as in the previous inventions, have
25 been obviated by the structure of the present invention. This allows the design of the present invention to include a greater liberality as far as spring sizes and strengths are concerned. Advantageously, the present invention provides a quick thrust of the lancet outwardly to penetrate
30 the skin of the patient, and then automatically retracts the lancet from the patient's skin so that dwell time therein is minimized. It is intended that this embodiment of the present invention can be economically fabricated so that it can be discarded after single use in disposable fashion.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view illustrating the preferred embodiment of the automatic retractable lancet assembly of the present invention;

5 Fig. 2 is an exploded assembly plan view of the elements of the automatic retractable lancet assembly of Fig. 1;

Fig. 3 is an enlarged end view of the slidable sleeve element taken along line 3-3 of Fig. 2;

10 Fig. 4 is an enlarged end view of the slidable sleeve element taken along line 4-4 of Fig. 2;

Fig. 5 is an enlarged end view of the skirt element of the preferred invention taken along line 5-5 of Fig. 2;

15 Fig. 6 is an enlarged end view of the depressible plunger element of the preferred invention taken along line 6-6 of Fig. 2;

20 Fig. 7 is a cross-sectional view of the automatic retractable lancet assembly taken along line 7-7 of Fig. 1 illustrated in position in conjunction with a finger of a patient;

Fig. 8 is a cross-sectional view of the lancet assembly of Fig. 7 illustrating the sequential operation of the assembly to penetrate the finger of the patient; and

25 Fig. 9 is a cross-sectional view of the lancet assembly of Figs. 7 and 8 illustrating the next sequential operative step after the lancet has been automatically retracted back into the assembly after the finger of the patient has been penetrated.

DETAILED DESCRIPTION

30 While this invention is satisfied by embodiments in many different forms, there is shown in the drawings and will herein be described in detail a preferred embodiment of the invention, with the understanding that the present disclosure is to be considered as exemplary of the principles
35 of the invention and is not intended to limit the invention to the embodiment illustrated. The scope of the invention

will
lents

part
an a
clea
the
ing:
seco
a sl
all
ly s
othe

tube
ope
dis
str
whe
thr
sir
per
the
42

sl
re
be

wa
wi
S

i
3

t

; f

1

will be measured by the appended claims and their equivalents.

Referring to the drawings, and Figs. 1 and 2 in particular, there is illustrated a preferred embodiment of an automatic retractable lancet assembly 20. As more clearly seen in Fig. 2, taken in conjunction with Fig. 1, the basic components of lancet assembly 20 are the following: a housing 22, a lancet 24, a first spring 26, a second spring 28, a depressible plunger 30, a skirt 32 and a slidable sleeve 34. In this embodiment being described, all of the aforementioned elements are preferably cylindrically shaped and designed for coaxial arrangement with each other as described below.

More specifically, housing 22 is an elongate hollow tube having a passageway 36 therethrough terminating in an opening 38 at its proximal end and an aperture 39 at its distal end. An annular flange 40 surrounds opening 38 for structural purposes in maintaining the elements together when assembled. In this particular embodiment, there are three longitudinal slots 41 (only two being shown in Fig. 2 since they are spaced approximately 120° apart) through the peripheral wall of housing 22. These slots terminate toward the distal end of the housing at slanted, inclined surfaces 42.

Lancet 24 includes a sharp point 44 extending from a slidable piston 46. As more clearly seen in Fig. 7 which represents the instant invention in the assembled condition before use, lancet 24 is slidably positioned inside passageway 36. The diameter of piston 46 is designed to slide within the inside diameter of passageway 36 of housing 22. Sharp point 44 faces toward aperture 39 and is maintained inside the housing adjacent the interior side of aperture 39. Second spring 28 is provided to maintain the lancet in this position. Spring 28 is basically a coil spring which fits around the sharp point of the lancet so that piston 46 rests upon this spring. An inwardly projecting lip 48 at

the distal end of the housing cooperates to hold the spring inside the housing. In this position as seen in Fig. 7, which represents the lancet assembly before use, spring 28 is in a substantially decompressed condition.

5 Slidable sleeve 34 is adapted to slide over housing 22 in coaxial fashion. This sleeve includes three flexible legs 50 spaced approximately 120° apart, as illustrated in Figs. 3 and 4, and adapted to correspond to slots 41 of the housing. Each flexible leg includes an inwardly projecting
10 foot 51 which projects through corresponding slot 41 in the housing. As seen in Fig. 7, feet 51 engage the top of piston 46 of the lancet. This engagement helps maintain the lancet in a relatively immobile position in the pre-use condition.

15 Skirt 32, also preferably cylindrically shaped, includes an upper portion 54 which is sized to snugly fit around flange 40 of the housing. The bottom portion of skirt 32 includes three flexible arms 55 extending downwardly, as seen in Fig. 5. Each arm 55 has at its distal
20 end a hook 56 projecting inwardly. In the assembled condition as seen in Fig. 7, skirt 32 is oriented so that arms 55 are peripherally offset from legs 50 of the slidable sleeve. In this manner, hooks 56 fit between legs 50 and engage the flat surfaces 58 on the sleeve between the legs.
25 This immobilizes slidable sleeve in a relatively fixed condition before the lancet assembly is used. In this condition, first spring 26 is compressed between the proximal end of slidable sleeve 22 and flange 40 of the housing. First spring 26 is essentially similar to second spring 28
30 inasmuch as it is a coil spring. This first spring is, however, larger in diameter and should be designed with a larger spring force inasmuch as it is the driving spring for rapidly thrusting the lancet through the skin of the patient. With the hooks at the end of the skirt engaging the flat
35 surfaces of the slidable sleeve, first spring 26 is effectively maintained in the compressed condition before use of this

lanc
7.

shap
prox
are
in F
22 i
61 i
axis
pro:
pro:
Fig
ori
dis
in
arm
64
fle
cli
dow
mat
in
Fig
the
fir
ass
anc
Fig
is
th
wa
ca
su
of

lancet assembly, as more clearly seen by referring to Fig. 7.

Depressible plunger 30 is preferably a cylindrically shaped plug with a flat push-button surface 60 at its proximal end. Depending from the distal end of plunger 30 are three equally spaced flexible arms 61, as illustrated in Fig. 6. Plunger 30 is slidably positioned inside housing 22 in the end opposite from the lancet so that flexible arms 61 project through slots 41 running along the longitudinal axis of the housing. In addition, flexible arms 61 also project through slots 62 which run longitudinally in the proximal portion of slidable sleeve 34 as illustrated in Fig. 4. Slots 62 are oriented to correspond with the orientation of slots 41 in the housing. Slots 62 terminate distally in slanted, inclined surfaces 64 which can be seen in Fig. 7. In the loaded condition before use, flexible arms 61 of the plunger may either contact inclined surfaces 64 or be slightly spaced therefrom. In either case, the flexible arms of the plunger are adapted to engage the inclined surfaces on the slidable sleeve when the plunger is downwardly depressed. Figs. 1 and 7 illustrate the automatic retractable lancet assembly of the present invention in the loaded condition as it would appear before use. In Fig. 7, a finger F of the patient is positioned adjacent the distal end of the assembly just before use so that the finger covers aperture 39. The operation of this lancet assembly, illustrating penetration of the skin of the finger and then automatic retraction of the lancet is seen in Figs. 8 and 9.

Turning to Fig. 8, in particular, lancet assembly 20 is shown in position on top of finger F of a patient, while the finger of the operator OF is illustrated pushing downwardly on depressible plunger 30. This downward movement causes flexible arms 61 of the plunger to engage inclined surfaces 64 on the slidable sleeve. Inasmuch as hooks 56 of the skirt maintain the slidable sleeve in a fixed posi-

tion, contact of flexible arms 61 against inclined surfaces 64 causes the arms to flex outwardly. This outward flexure causes contact with flexible arms 55 of the skirt. In turn, flexible arms 55 flex outwardly a sufficient amount so that hooks 56, at the end of flexible arms 55, become disengaged from flat surfaces 58 on the slidable sleeve. Once this disengagement occurs, there is no force tending to compress spring 26 into the compressed condition. As a result, with the restraining force removed, the spring is released causing an expansion of the spring. This expansion causes sleeve 34 to move distally within housing 22 in a rapid thrusting movement. Inasmuch as feet 51 at the distal end of the sleeve are in engagement with the piston portion of lancet 24, the lancet also moves distally. Sharp point 44 moves rapidly out of aperture 39 and penetrates finger F positioned just under the aperture. While this is occurring, it is noted that the distal movement of lancet 24 has caused second spring 28 to become compressed. This compression is a direct result of the energy transmitted to slidable sleeve 34 by the release of first spring 26. In order to assure proper compression of second spring 28, it is desirable that the first or driving spring have a higher spring constant than the second or return spring.

In addition to causing downward movement of lancet 24 and compression of second spring 28, the downward or distal movement of slidable sleeve 34 causes flexible legs 50 to engage inclined surfaces 42 on housing 22. As a result, the downward movement of flexible legs 50 against inclined surfaces 42 causes these flexible legs to flex outwardly. As a consequence, inwardly projecting feet 51 become disengaged from the piston portion of lancet 24. This condition is more clearly seen by referring to Fig. 9. Inasmuch as feet 51 serve as the restraining force against second spring 28 when compressed, the disengagement of these feet from the lancet effects a release of this spring. This in turn causes an expansion of spring 28 thereby rapidly re-

tracting lancet 24 back inside the housing. It is noted that when spring 28 expands its entire energy is transmitted only to lancet 24 to effect its retraction back inside the housing. With feet 51 disengaged, slidable sleeve 34 also becomes dissociated from the retraction movement of the lancet caused by expansion of second spring 28. Therefore, when second spring 28 expands, it is not working against the decompressed state of first spring 26 since the disengagement of feet 51 dissociate the entire slidable sleeve and first spring 26 from the retraction movement of the lancet and the decompression of second spring 28. Accordingly, with a low amount of energy required to retract the lancet back inside the housing, second spring 28 can be a small, lightweight and inexpensive spring. It is appreciated that the structure of the present lancet assembly causes not only the rapid thrusting movement of the lancet to penetrate the skin of the patient, but also effects the automatic retraction of the lancet back inside the housing of the assembly. Thus, downward depression of plunger 30 is the stimulus for both outward release and inward retraction of the lancet. Insofar as a preferred embodiment of the present invention is intended to be disposable, the housing, slidable sleeve, flexible skirt and depressible plunger can be fabricated of inexpensive plastic materials. On the other hand, lightweight metals can be employed for the lancet and the two springs described above.

Thus, there has been provided in accordance with the present invention an automatic retractable lancet assembly. While two springs are preferably employed, the return spring operates independently and dissociated from any movement of the driving spring. Accordingly, balance of spring forces is not required as in prior art lancet assemblies. This allows more straightforward operation, reduction of spring sizes and lighter weight materials.

WHAT IS CLAIMED IS:

1. An automatic retractable lancet assembly (20) comprising:

a housing (22) having an aperture (39);

a lancet (24) movably mounted in said housing (22) with
its point (44) lying adjacent the interior side of said
aperture (39);

a depressible plunger (30) movably mounted in said housing
(22) in the end thereof opposite from said lancet (24);

a first spring (26) mounted inside said housing (22)
in a compressed condition and adapted to decompress upon
said plunger (30) being depressed into said housing (22)
and cause the movement of said lancet (24) outward of said
aperture (39) for penetration of the skin of a patient,
said first spring (26) adapted to become dissociated from
said lancet (24) after said lancet completes its outward
movement; and

a second spring (28) mounted inside said housing (22)
in a substantially decompressed condition before said plunger
(30) is depressed, adapted to become compressed during
outward movement of said lancet (24) and further adapted
to decompress when said first spring (26) becomes disso-
ciated from said lancet (24) to cause said lancet to be
automatically retracted back inside said housing (22).

2. The assembly of Claim 1 wherein said plunger (30) is
mounted coaxially inside said housing (22).

3. The assembly of Claim 1 wherein a slidable sleeve (34)
is positioned on said housing (22) for moving said lancet
(24) outwardly upon decompression of said first spring
(26).

4. The assembly of Claim 3 wherein said sleeve (34) is positioned to restrain said first spring (26) in a compressed condition before said plunger (30) is depressed.

comprising:

(22) with

of said

5

said housing

(24);

g (22)

ss upon

ng (22)

10

d of said

tient,

ted from

outward

15

ng (22)

said plunger

during

adapted

disso-

to be

20

(22).

30) is

sleeve (34)

d lancet

25

spring

30

5. The assembly of Claim 4 wherein a flexible skirt (32) is positioned on said housing (22) for maintaining the sleeve (34) in position for compressing said first spring (26).

6. The assembly of Claim 5 wherein said plunger (30) includes a plurality of flexible arms (61) adapted to flex outwardly upon depression of said plunger (30) and contact said flexible skirt (32) and cause said skirt (32) to flex outwardly to thereby become disengaged from said sleeve (34) thereby releasing the restraining force applied to said first spring (26) so that said sleeve (34) moves distally to cause outward movement of said lancet (24).

7. The assembly of Claim 6 wherein said sleeve (34) includes a plurality of inclined surfaces (64) adapted to be engaged by said flexible arms (61) upon depression of said plunger (30) for causing said flexible arms (61) to flex outwardly.

8. The assembly of Claim 3 wherein said housing (22) includes openings (41) around its periphery and said sleeve (34) includes a plurality of feet (51) each extending through one of said openings (41) for engaging said lancet (24).

9. The assembly of Claim 8 wherein said feet (51) are included on a plurality of flexible legs (50) on said sleeve (34), said legs (50) adapted to flex outwardly upon distal movement of said sleeve (34) whereby said feet (51) become disengaged from said lancet (24) after said second spring (28) has become compressed, said disengagement of said feet (51) thereby releasing the restraining force applied

-12-

to said second spring (28) so that said second spring (28) becomes decompressed and thereby automatically retracts said lancet (24) back inside said housing (22).

5 10. The assembly of Claim 9 wherein said housing (22) includes a plurality of inclined surfaces (42) adapted to be engaged by said flexible legs (50) upon distal movement of said sleeve (34) for causing said legs (50) to flex outwardly.

10 11. The assembly of Claim 1 wherein said housing (22) is substantially cylindrically shaped.

12. The assembly of Claim 1 wherein said housing (22) and said plunger (30) are made of plastic and said lancet (24) 15 is made of metal.

15 13. An automatic retractable lancet assembly (20) comprising:

a housing (22);

a sharp-pointed lancet (24) movably mounted inside said housing (22);

20 means for actuating the movement of said lancet (24) outwardly from said housing (22) and for thereafter becoming dissociated from further movement of said lancet (24); and

25 means operable subsequent to the outward movement of said lancet (24) for automatically retracting said lancet (24) back inside said housing (22).





14. An automatic retractable lancet assembly (20) comprising:

a substantially cylindrical housing (22) having an aperture (39);

30 a sharp-pointed lancet (24) movably mounted in said housing (22) with its point (44) lying adjacent the interior

d spring (28) side of said aperture (39);
y retracts a depressible plunger (30) coaxially mounted inside
) . said housing (22) in the end thereof opposite from said
ing (22) in- 5 adapted to flex outwardly upon depression of said plunger
adapted to (30);
stal movement a first spring (26) mounted inside said housing (22)
) to flex restrained in a compressed condition, before said plunger
10 on said housing (22), said sleeve (34) including a plurality
ing (22) is of flexible legs (50) each having a projecting foot (51)
thereon for engaging said lancet (24);
ing (22) and a flexible skirt (32) positioned on said housing (22)
d lancet (24) 15 for maintaining the sleeve (34) in position for compressing
said first spring (26) and adapted to flex outwardly upon
the outward flexing of said plunger arms (61) so that said
skirt (32) becomes disengaged from said sleeve (34) to
(20) compris- release the restraining force applied to said first spring
(26) causing said sleeve (34) to move distally and thereby
20 move said lancet (24) outwardly from said housing (22);
and
l inside said a second spring (28) mounted inside said housing (22)
lancet (24) in a substantially decompressed condition before said plunger
after be- (30) is depressed adapted to become compressed after said
id lancet 25 sleeve (34) moves distally and causes outward movement
of said lancet (24), said flexible legs (50) of said sleeve
(34) adapted to flex outwardly after distal movement of
vement of said sleeve (34) whereby said feet (51) become disengaged
said lancet from said lancet (24) after said second spring (28) has
30 become compressed, said disengagement of said feet (51)
thereby releasing the restraining force applied to said
20) compris- second spring (28) so that said second spring (28) becomes
decompressed and thereby automatically retracts said lancet
ving an (24) back inside said housing (22).

in said
the interior






FIG. 2

FIG. 5




FIG. 6




FIG. 7




FIG. 8

